





Transmission Fluid











- Manufacturing and trading of Base oil SN 500, SN 300, SN 150
- Manufacturing and trading of Automotive and Industrial Lubricants
- Trading of Diesel, Furnace oil, Fuel oil, Kerosene etc.
- Fuel supply to major domestic industries
- Fuel bunkering to Vessels











GASOLINE ENGINE OIL

Full synthetic oil

SAE: 5W30, SAE: 5W40, API: SM/CF

Sharafco fully synthetic multi grade multipurpose engine oil is specially formulated with full synthetic base oil and high quality additives for ultimate engine protection and performance. It is used for various kinds of gasoline engines and diesel engines like passenger and racing cars, light trucks and all makes

of American, European and Japanese cars. It gives ultimate engine protection in all driving conditions and low viscosity, rapid oil flow, low friction effectively contributes towards reducing fuel consumption. Fully synthetic oil can be used for all naturally aspirated, fuel injected, turbo charged and multivalve passenger car engines.

Packing size (Plastic & Metal): 12x1 ltr, 24x1 ltr, 6x4 ltr, 6x5 ltr 10 ltr, 20 ltr, 25 ltr, 208 ltr





GASOLINE ENGINE OIL

Semi synthetic oil

SAE: 10W40, API: SL/ CF

Sharafco semi synthetic multi grade and multipurpose gasoline engine oil manufacture from high quality synthetic and mineral base oils with selected additives. It is recommended for various kinds of gasoline engines and diesel engines like passenger and racing cars, light trucks and all makes of American, European and Japanese cars. It assures excellent engine protection in severe weather conditions, Longer drain interval, Low oil consumption and oxidation stability and it protect engine completely against wear, rust, corrosion, heat stress and engine deposits.

Packing size (Plastic & Metal): 12x1 ltr, 24x1 ltr, 6x4 ltr, 6x5 ltr 10 ltr, 20 ltr, 25 ltr, 208 ltr



GASOLINE ENGINE OIL

Mono Grade: SAE: 30, SAE: 40, SAE: 50, SAE: 60 Multi Grade: 10W40, 15W40, 15W50, 20W40, 20W50

API: SM/CF, SL/CF, SJ/CF, SG/CF, SF/CD

Sharafco mono grade and multi grade gasoline engine oil manufactured from high quality virgin base oil with European additives and it meets API standard. It is specially manufactured for all kind of passenger car, van, light truck, heavy trucks of gasoline engine and diesel engine. It assures excellent engine protection in severe weather conditions, Longer drain interval, Low oil consumption and oxidation stability and it protect engine completely against wear, rust, corrosion, heat stress and engine deposits.

Packing size (Plastic & Metal): 12x1 ltr, 24x1 ltr, 6x4 ltr, 6x5 ltr, 10 ltr 20 ltr, 25 ltr, 208 ltr





DIESEL ENGINE OIL

SAE: 30, SAE: 40, SAE: 50, SAE: 60

API: CI-4, CH-4, CG-4, CF-4, CF, CD, CB, CC.

Sharafco diesel engine oil manufactured from high quality virgin base oil and European additives and it meets API standard. It is specially manufactured for all kind of passenger car, van, light truck, heavy trucks of diesel engines. It gives excellent engine protection in severe weather conditions, Longer drain interval, Low oil consumption and oxidation stability and completely protects engine against wear, rust, corrosion, heat stress and engine deposits.

Packing size (Plastic & Metal): 12x1 ltr, 24x1 ltr, 6x4 ltr, 6x5 ltr 10 ltr, 20 ltr, 25 ltr, 208 ltr





GEAR OIL

SAE: 80W90, 85W140, 140, 90

API: GL-1, GL-4, GL-5

Sharafco Gear oil manufactured from high quality virgin base oil and selected extreme pressure additives which allows maximum protection for automotive gears and industrial gears. It protects the gear from rust & corrosion and low temperature properties, also gives good start in cold weather. It is suitable for highly stressed gear boxes running at high temperatures.

Packing size (Plastic & Metal): 12x1 ltr, 24x1 ltr, 6x4 ltr, 6x5 ltr

10 ltr, 20 ltr, 25 ltr, 208 ltr





HYDRAULIC OIL

ISO: 22, 32, 46, 68, 100, 150

Sharafco premium quality hydraulic oil formulated from high quality base oil and combined with anti wear high quality additives system that protects against wear, rust and corrosion. It is used in all kind of hydraulic system running under the most severe conditions, such as machine tools, mould injection machines, presses, piston and gear pump, heavy hydraulic equipments and many kinds of industrial and construction equipments and machineries.

Packing size (Plastic & Metal): 12x1 ltr, 24x1 ltr, 6x4 ltr, 6x5 ltr 10 ltr, 20 ltr, 25 ltr, 208 ltr





AUTOMATIC TRASMISSION FLUID (ATF)

Type - A, Dex-II, Dex-III

Sharafco superior quality automatic transmission fluid formulated with high viscosity index base oils and selective additive package to obtain anti-wear, anti-oxidant, anti-foam properties and low temperature fluidity. It provides excellent protection against wear and its frictional properties gives consistent and smooth shift under a wide range of driving condition. It is specially engineered for passenger cars, light trucks and commercial vehicles automatic transmission, hydraulic systems of mobile and off high way equipment and industrial applications.

Packing size (Plastic & Metal): 12x1 ltr, 24x1 ltr, 6x4 ltr, 6x5 ltr 10 ltr, 20 ltr, 25 ltr, 208 ltr



DOT-3, DOT-4

SAE: J 1704, ISO 4925 FMVSS 116

Sharafco brake fluid blended from glycol ethers and polygly-cols. It is formulated to contain oxidation and corrosion inhibitors to enhance its chemical stability and recommended to use in automotive drum and disc brake systems. It will provide a safety against brake fade where abnormal high system temperatures are generated by heavy duty vehicle operation.

Packing size: 24x250 ml, 24x500 ml





MARINE ENGINE OIL

SAE: 30, 40, 50

Sharafco marine engine oil assures a high level of detergency, disperancy and alkalinity due to its high TBN and sulphate ash content. It is formulated with high quality base oils in conjunction with the latest additives technology to deliver a high load carrying capacity, excellent oxidation and a high level of alkalinity retention. It is highly recommended for marine and industrial diesel engines including turbo charged models operating in all type of conditions.

Packing size (Plastic & Metal): 12x1 ltr, 24x1 ltr, 6x4 ltr, 6x5 ltr 10 ltr, 20 ltr, 25 ltr, 208 ltr





OUTBOARD ENGINE OIL

API: TC-W3, SAE: 30

Sharafco outboard engine oil is ashless lubricating oil formulated to meet the critical requirements of high performance, water cooled two stroke engines. It is formulated to minimize deposit formation, spark plug fouling and preignition, prevent rusting and control wear.

Packing size (Plastic & Metal): 12x1 ltr, 24x1 ltr, 6x4 ltr, 6x5 ltr 10 ltr, 20 ltr, 25 ltr, 208 ltr















TO REACH US...

Sharafco Oil Refinery & Ind. Co. LLC

Tel: +971 6 5310786, Fax: +971 6 5310787 P.O. Box 43786, Behind Sharjah Cement Factory Al Sajja Ind. Area, Sharjah, U.A.E. E-mail: info@sharafcogroup.com

Sharafco Engineering. Ind. LLC

Tel: +971 6 5310905, Fax: +971 6 5310906 P.O. Box 43786, Behind Sharjah Cement Factory Al Sajja Ind. Area, Sharjah, U.A.E. E-mail: info@sharafcogroup.com

Sharafco Petroleum FZC

Tel: +971 6 5310786, Fax: +971 6 5310787
P.O. Box 41914, Hamriyah Free Zone, Sharjah, U.A.E.
E-mail: sharaf@sharafcogroup.com

Visit us: www.sharafcogroup.com



